

Condensation dryer AD 780-P



Features

- Completely protected in an impact-resistant plastic casing:
 - Axial fan with aluminium fan wheel (with winding protection).
 - Fully hermetically sealed rotary compressor, protected against overloading, vibration-insulated bearings.
- Condenser and evaporator: copper piping covered with aluminium fins. Cooling circuit: copper piping with capillary tube and filter dryer. Service connector on suction side.
- Automatic hot-gas defrosting, controlled by Dry-Logic.

Application & functioning

Mode of functioning

Condensation principle
(heat-pump technology with energy recovery)

Area of use

Closed rooms (water works, water damage drying, storing, archives, ect.)

Suitable for

Heated rooms up to 950 cbm **
Unheated rooms up to 600 cbm **

Dimensions & installation

Installation / mobility

On the floor. Ergonomically designed casing for easy transport, integrated push-handle, two big wheels (D= 300 mm). The devices are stackable for storage purposes.

Initiation

Put plug into power socket. Switch the dryer on at On/Off-switch and set the required humidity at the hygostat.

Condensate outlet

Installed condensate pump. Max. height level: 4 mtrs.
Switch for manually pump off (before transport)

Air flow

Air inlet at the back side via air filter, air outlet on the front (draught-free, through slanted fins)

Maintenance

clean / change air filter

Dimensions

Height / width / depth:
1.000 mm / 640 mm / 580 mm

Weight

57 kg

Technical data

Casing

Impact-resistant plastic (grey, RAL 7001, PE polyethylene DIN 16776), operating panel (RAL 1023) and air inlet/outlet (RAL 7021): galvanised sheet steel, flux-coated, protection class: IP 14

Dehumidifying performance / Power consumption*

at 30°C / 80% r.h. = 78,0 l/24h / 1.250 Watts/h
at 27°C / 60% r.h. = 52,0 l/24h / 1.090 Watts/h
at 20°C / 60% r.h. = 35,0 l/24h / 900 Watts/h
at 10°C / 70% r.h. = 20,0 l/24h / 720 Watts/h

Air circulation rate

820 cbm/h

Operation range

Temperature: +3°C up to +32°C
Humidity: 40%r.h. up to 95% r.h.

Noise level

53 dB (A)

Voltage

230 V / 50 Hz, Fusing: 10 A slow

Conneting cable

5 mtrs. with plug, cable keeper

Refrigerant

R407c

Control elements

On-/Off-Switch, orange, illuminated; neons for „defrost mode“, „humidity ok“ and „pump fault“; operation time counter; hygostat with knob

Optionally available accessories

Condensate hose 15 x 2 mm,
Combi-Counter (h and kWh)